Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile



Incubadora temp y humedad 250lts,Temp:con humidificacion:10-60°C y sin:5-65°C

Código: B-01-29-000205-0002

Marca: Belltronic

Ver producto en Cotecno | Solicitar cotización

Detalle | Especificaciones | Aplicaciones | Galería de imágenes

Detalle

Descripción general

Introduction ..... 1 II.Characteristics ..... 2 III. Main technical parameters ..... 3 1.Working room temperature profile..... 3 2.Temperature and humidity diagram ..... 4 IV.Working Condition ..... 4 V.Attentions ..... 4 VI.Operation Instruction ..... 5 1 .Instructions for use ..... 5 2. Operation step ..... 5 3.Operation and display instructions of Meter..... 6 3.1 definition ..... 6 3.2□Display windo ..... 6 3.3□Definition of keys ..... 7 3.4 Operation and Usage ..... 7 3.4.1□Power on the controller ..... 7 3.4.2□Modification of setting value ..... 7 3.4.3□Set segment number or cycle. ..... 8 3.4.4□Start and Stop ..... 8 3.4.5□Reservation Function ..... 8 3.4.6□Fault Prompt ..... 9 3.4.7□Defrost function..... 9 3.4.8□Power off memory function ..... 9 3.4.9 Check and set the internal parameters ..... 9 4 Parameters' tables..... 9 5. instrument wiring diagram ..... 19 6.General faults and troubleshooting ..... 19 I. Introduction The BE-BoIncTemHuCon model Constant Temperature and Humidity Incubator is the ideal testing equipment for natural environment simulation. With 30 segments of program memory, it comes with functions of constant temperature, auto humidity control, day / night cycle, and over-temperature protection. Its applications range from seed germination, seedling raising, plant growth, microorganism cell culturing, and insects rearing to commercial medicinal, building and timber material performance testing, as well as industrial product quality inspection and constant temperature and humidity experiment. II.Characteristics 1. High-brightness large screen liquid crystal display panel and light-touching operational key, in which cycle period, segments, time, temperature, humidity are display clearly at a glance. It can be connect with computer through RS232 interface, which ensures the whole experiments process controlled in a safety state. 2. Reliable security; the instrument has diverse of anti-jamming measures and has function of over-temperature protection, thermal resistor short-circuit protection and delay protection. 3. The whole structure is made with advanced technique. Cold rolling steel Surface with electrostatic spraying surface which is attractive and durable. 4. Advanced air flue circulate mode, which ensures balanced flow rate in working room and prevents powdery substance, Young plants from blowing away. World famous brand compressor; environmental protection refrigerant R134a is reliable, it ensures experiment goes on safely and effective. Options: ① RS-485/232 interface and supervisory computer control software. ② Printer(miniature) ③ Power failure alarm ④ Leakage protection ⑤ Danfoss compressor The above option should be ordered and produced in our company. III. Main technical parameters Model BE-BoIncTemHuCon70B BE-BoIncTemHuCon150B BE-

Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile

BoIncTemHuCon250B Supply power 220V/50Hz Temp. range With humidification 10-65 ℃ without humidification : 0-65 ℃ Temp. Distinguish 0.1℃ ability Temp. fluctuation High Temp ± 1℃ Low Temp ±0.5℃ Humidity range 45%~90%RH Humidity error ±5%~8% RH Heating power 500W 800W 1200W Interior 420*350*500 500*400*750 500*500*950 dimensions(mm) Exterior dimensions 570*560*1020 640*620*1270 660*700*1470 (mm) Packaging 730*720*1170 820*760*1430 880*825*1645 dimensions(mm) N.W. (KG) 59.5 68.5 71.5 G.W. (KG) 85.5 92.5 115.5 1.Working room temperature profile Temp. spot Temp(℃) Temp. spot Temp(℃) ① 36.63 ⑤ 36.91 ② 36.98 ⑥ 36.86 ③ 37.5 ⑦ 36.88 ④ 37.33 ⑧ 36.64 ⑨ 37.15 Diagram: Cooling down speed (SPC-250) Heating up speed (SPX-250) Note: The above specification are tested under chamber temperature ≤25℃, it is just usable for our products. 2.Temperature and humidity diagram IV.Working Condition 1. Ambient temperature:5℃~32℃(e.g. set temperature≤10℃, ambient temperature≤28℃) 2. Relative humidity: ≤80%RH 3. Air pressure: 86-10Kpa 4. Keep the climate chamber away from vibration and corrosive gas. 5. Keep the container away from direct sunlight and other cooling and heating source. 6. Keep it away from high concentration of stove; install it horizontally and leave some space between machine and wall. 7. Install it in room with good ventilation. V.Attentions Safety Attentions 1. Connect the device to an earthed power supply to ensure...

Modelo legacy: B-01-29-000205-0002.

Especificaciones técnicas

Especificación	B-01-29-000205-0002
Tipo	Incubadoras de cultivo
Capacidad	250 L
Temperatura minima	10 °C
Temperatura maxima	65 °C
Fluctuacion temperatura	±0.5 °C
Precision temperatura	±0.5 °C
Humedad	Con control de humedad
Iluminacion	Sin iluminacion
Agitacion	Sin agitacion
CO2	Sin CO2
Alimentacion	220 V

Aplicaciones

- Uso de laboratorio
- Control de calidad

Galería de imágenes

Mostrando hasta 6 imágenes de la galería.



Imagen de galería 1

Siguiente paso: ver producto en Cotecno | solicitar cotización