Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile



4.5" Relative Humidity Probe RHP-SW-B

Código: RHP-SW-B

Marca: Tramex

Ver producto en Cotecno | Solicitar cotización

Detalle | Especificaciones | Aplicaciones | Galería de imágenes

Detalle

The Tramex Relative Humidity Probes are the most advanced, resilient and re-usable RH probe on the market today, allowing the user to evaluate moisture conditions within the building structure. The different lengths and thicknesses make them ideal for use by Flood and Water Damage Restoration as well as Building Survey professionals. The probes, which house the latest Hygro-i2 technology, measure Relative Humidity, Temperature, Dewpoint temperature and grains per pound humidity ratio. The probes can be used for the evaluation of moisture conditions of wall and cavity structures as well as ambient air conditions within the building envelope. The speed and accuracy of the Tramex Hygro-i2® probes set them apart from all other RH probes on the market. The confidence in knowing you are testing with the best and fastest RH probe brings reliability and peace of mind to a whole new level.

For use with CMEX5, MEX5 and Feedback Datalogger RHTX.

- Fast Acclimation and Temperature response time.
- Proven robustness, Durable and Reusable.
- Best in class accuracy and reliable, even at high RH >90%.
- Measures giving in situ relative humidity and ambient RH, temperature, dew point temperature & grains per pound.
- Relative Humidity range: 0% to 100%
- Temperature Range: -4ºF to 158ºF(-20°C to 70°C)
- Best temperature accuracy of ±0.1ºF Range -4ºF to 158ºF(±0.1 °C Range -20°C to 70°C)

Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile

Galería de imágenes

Mostrando hasta 6 imágenes de la galería.



Imagen de galería 1

Siguiente paso: ver producto en Cotecno | solicitar cotización