Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile

Unbonded Capping Retainers

Código: B-01-200-0132

Marca: Belltronic

Ver producto en Cotecno | Solicitar cotización

Detalle | Especificaciones | Aplicaciones

Detalle

Computerized Compression Machine 2000Kn Fully Automatic laboratorio de ingenieria civil.

Contenido estructurado en formato Aurora a partir de tablas tecnicas del proveedor.

Quick Buying Guide

1. Define required test standard and sample size.
2. Choose capacity/temperature/range according to your daily workload.
3. Select accessories only if they are needed for your lab routine.

Common selectable options:

- · 100 mm Cube Lower Platen Piece
- · Standard Distance Piece Ø198 x 50 mm
- · Portable Flexural Test Device
- NLT-CON-4000-X-DS1

- **Max. Vertical Clearance:** 382 mm
- **Max. Horizontal Clearance:** 270 mm
- **Capacity:** 2000 kN
- **Compression Platen Diameter:** 295 mm
- **Piston Ram Diameter:** 250 mm
- **Piston Ram Travel:** 60 mm
- **Column Diameter:** Ø70 mm
- **Accuracy:** Class 1

Especificaciones técnicas

Variant	Internal Code	Supplier Model
· 100 mm Cube Lower Platen Piece	NLT-CON-4000-X-002	
· Standard Distance Piece Ø198 x 50 mm	NLT-CON-4000-X-004	
· Portable Flexural Test Device	NLT-CON-4000-X-016	
NLT-CON-4000-X-DS1	NLT-CON-4000-X-DS1	
NLT-CON-4000-X-DS2	NLT-CON-4000-X-DS2	

Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile

Variant	Internal Code	Supplier Model
· 100/250 kN Hydraulic Flexural Frame	NLT-CON-4008-X-001	
· Split Tensile Test Device	NLT-CON-4012-X-003	

Aplicaciones

Use this section to match lab workflow, sample throughput, and required test standards.

1. Define the required test family and expected daily volume.
2. Choose the variant with the closest technical range and dimensions.
3. Add only accessories that are required for your workflow.

Variant guidance:

- **· 100 mm Cube Lower Platen Piece:** use this option when its capacity/range matches your test routine.
- **· Standard Distance Piece Ø198 x 50 mm:** use this option when its capacity/range matches your test routine.
- **· Portable Flexural Test Device:** use this option when its capacity/range matches your test routine.
- **NLT-CON-4000-X-DS1:** use this option when its capacity/range matches your test routine.
- **NLT-CON-4000-X-DS2:** use this option when its capacity/range matches your test routine.
- **· 100/250 kN Hydraulic Flexural Frame:** use this option when its capacity/range matches your test routine.

Siguiente paso: ver producto en Cotecno | solicitar cotización