Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile



Portafiltros de gran capacidad

Marca: STERLITECH

Ver producto en Cotecno | Solicitar cotización

Códigos de variantes

Referencia	Código
1	17302390
2	301506
3	301706
4	301727
5	301804
6	301905
7	301926
8	301990
9	302002
10	306108

Detalle | Especificaciones | Aplicaciones

Detalle

Large Portafiltros

Producto publicado con base en la ficha vigente del proveedor Sterlitech.

SKU	Nombre proveedor	Fabricante	Categoría proveedor	Fuente
17302390	KST 142, SS Holder with Multimedia Portafiltro and 1.5L Reservoir, 304 SS	Advantec	Portafiltros /// Pressure Portafiltros	Ficha proveedor
301506	O-ring (FPM), KST 47 (47mm), Portafiltro with Reservoir	Advantec	Portafiltros /// Pressure Portafiltros	Ficha proveedor
301706	O-ring (FEP-encapsulated silicone), KST 90 (90mm)	Advantec	Portafiltros /// Pressure Portafiltros	Ficha proveedor

Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile

SKU	Nombre proveedor	Fabricante	Categoría proveedor	Fuente
301727	Back pressure support screen (PTFE coated 304 SS), KST 90 (90mm)	Advantec	Portafiltros /// Pressure Portafiltros	Ficha proveedor
301804	Support screen (PTFE coated SS), KST 90 (90mm)	Advantec	Portafiltros /// Pressure Portafiltros	Ficha proveedor
301905	O-ring (silicone), KST 142 (142mm)	Advantec	Portafiltros /// Pressure Portafiltros	Ficha proveedor
301926	Back pressure support screen (304 SS), KST 142 (142mm)	Advantec	Portafiltros /// Pressure Portafiltros	Ficha proveedor
301990	Multi-Media Pressure Sealing Holder, 142mm	Advantec	Portafiltros /// Pressure Portafiltros	Ficha proveedor
302002	Underdrain support (316 SS), KST 142 (142mm)	Advantec	Portafiltros /// Pressure Portafiltros	Ficha proveedor
306108	Inlet cap gasket/O-ring (silicone), KST 47 (47mm)	Advantec	Portafiltros /// Pressure Portafiltros	Ficha proveedor

Especificaciones técnicas

Familia Odoo	Large Portafiltros
Fichas fuente	10

17302390

SKU Sterlitech	17302390
Ficha del fabricante	KST 142, SS Holder with Multimedia Portafiltro and 1.5L Reservoir, 304 SS
URL fuente	

Datos visibles del fabricante

KST 142, SS Holder with Multimedia Portafiltro and 1.5L Reservoir, 304 SS Sterlitech large Acero inoxidable Portafiltros with reservoirs are ideal for sterilizing and ultra-cleaning as well as for flow decay tests for pilot studies. SKU: 17302390 Brand: Advantec Diameter (mm): 142 Material Type: 304 Acero inoxidable Model: KST 142

Contenido visible del fabricante

Especificaciones KS 90 KS 90 ST KS 142 KS 142 ST KS 293 KS 293 ST KS 90 UH KS 142 UH KS 293 UH KST 47 KST 90 KST 142 Tamaño de filtro (mm) 90 142 293 90 142 293 47 90 142 Body 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 SS 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable O-ring & Gasket Silicone and PTFE Silicone and PTFE Silicone and PTFE Silicone Silicone Silicone Silicone and PTFE Silicone and PTFE Silicone and PTFE Inlet/Outlet ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 5/8” hose barb ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 16 mm hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter Max Pressure Inlet (psi) 99 99 99 99 99 99 71 71 71 Max Pressure Diff. (psi) <42 <42 <42 <42 <42 <42 <42 <42 <42 Filtration Area (cm 2) 45.3 113 530 45.3 113 530 12.5 43 113 Applications In-line gas or liquid filtration Ultraclean or sterilize gas or liquids Flow decay tests for pilot studies Hazardous toxicity testing and TCLP

Tabla fuente 1

	KS 90 KS 90 ST	KS 142 KS 142 ST	KS 293 KS 293 ST	KS 90 UH	KS 142 UH	KS 293 UH	KST 47	KST 90	KST 142

Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile

Tamaño de filtro (mm)	90	142	293	90	142	293	47	90	142
Body	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 SS	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable
O-ring & Gasket	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE	Silicone	Silicone	Silicone	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE
Inlet/Outlet	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 5/8” hose barb	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 16 mm hose barb adapter	¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter
Max Pressure Inlet (psi)	99	99	99	99	99	99	71	71	71
Max Pressure Diff. (psi)	<42	<42	<42	<42	<42	<42	<42	<42	<42
Filtration Area (cm 2)	45.3	113	530	45.3	113	530	12.5	43	113

301506

SKU Sterlitech	301506
Ficha del fabricante	O-ring (FPM), KST 47 (47mm), Portafiltro with Reservoir
URL fuente	

Datos visibles del fabricante

O-ring (FPM), KST 47 (47mm), Portafiltro with Reservoir SKU: 301506 Brand: Advantec Size (mm): 47

Contenido visible del fabricante

Especificaciones KS 90 KS 90 ST KS 142 KS 142 ST KS 293 KS 293 ST KS 90 UH KS 142 UH KS 293 UH KST 47 KST 90 KST 142 Tamaño de filtro (mm) 90 142 293 90 142 293 47 90 142 Body 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 SS 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable O-ring & Gasket Silicone and PTFE Silicone and PTFE Silicone and PTFE Silicone Silicone Silicone Silicone and PTFE Silicone and PTFE Silicone and PTFE Inlet/Outlet ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 5/8” hose barb ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 16 mm hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter Max Pressure Inlet (psi) 99 99 99 99 99 99 71 71 71 Max Pressure Diff. (psi) <42 <42 <42 <42 <42 <42 <42 <42 <42 Filtration Area (cm 2) 45.3 113 530 45.3 113 530 12.5 43 113 Applications In-line gas or liquid filtration Ultraclean or sterilize gas or liquids Flow decay tests for pilot studies Hazardous toxicity testing and TCLP

Tabla fuente 1

	KS 90 KS 90 ST	KS 142 KS 142 ST	KS 293 KS 293 ST	KS 90 UH	KS 142 UH	KS 293 UH	KST 47	KST 90	KST 142
Tamaño de filtro (mm)	90	142	293	90	142	293	47	90	142
Body	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 SS	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable
O-ring & Gasket	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE	Silicone	Silicone	Silicone	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE

Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile

Inlet/Outlet	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 5/8” hose barb	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 16 mm hose barb adapter	¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter
Max Pressure Inlet (psi)	99	99	99	99	99	99	71	71	71
Max Pressure Diff. (psi)	<42	<42	<42	<42	<42	<42	<42	<42	<42
Filtration Area (cm 2)	45.3	113	530	45.3	113	530	12.5	43	113

301706

SKU Sterlitech	301706
Ficha del fabricante	O-ring (FEP-encapsulated silicone), KST 90 (90mm)
URL fuente	

Datos visibles del fabricante

O-ring (FEP-encapsulated silicone), KST 90 (90mm) SKU: 301706 Brand: Advantec Size (mm): 90

Contenido visible del fabricante

Especificaciones KS 90 KS 90 ST KS 142 KS 142 ST KS 293 KS 293 ST KS 90 UH KS 142 UH KS 293 UH KST 47 KST 90 KST 142 Tamaño de filtro (mm) 90 142 293 90 142 293 47 90 142 Body 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 SS 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable O-ring & Gasket Silicone and PTFE Silicone and PTFE Silicone and PTFE Silicone Silicone Silicone Silicone and PTFE Silicone and PTFE Silicone and PTFE Inlet/Outlet ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 5/8” hose barb ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 16 mm hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter Max Pressure Inlet (psi) 99 99 99 99 99 99 71 71 71 Max Pressure Diff. (psi) <42 <42 <42 <42 <42 <42 <42 <42 <42 Filtration Area (cm 2) 45.3 113 530 45.3 113 530 12.5 43 113 Applications In-line gas or liquid filtration Ultraclean or sterilize gas or liquids Flow decay tests for pilot studies Hazardous toxicity testing and TCLP

Tabla fuente 1

	KS 90 KS 90 ST	KS 142 KS 142 ST	KS 293 KS 293 ST	KS 90 UH	KS 142 UH	KS 293 UH	KST 47	KST 90	KST 142
Tamaño de filtro (mm)	90	142	293	90	142	293	47	90	142
Body	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 SS	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable
O-ring & Gasket	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE	Silicone	Silicone	Silicone	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE
Inlet/Outlet	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 5/8” hose barb	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 16 mm hose barb adapter	¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter
Max Pressure Inlet (psi)	99	99	99	99	99	99	71	71	71
Max Pressure Diff. (psi)	<42	<42	<42	<42	<42	<42	<42	<42	<42

Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile

Filtration Area (cm 2)	45.3	113	530	45.3	113	530	12.5	43	113

301727

SKU Sterlitech	301727
Ficha del fabricante	Back pressure support screen (PTFE coated 304 SS), KST 90 (90mm)
URL fuente	

Datos visibles del fabricante

Back pressure support screen (PTFE coated 304 SS), KST 90 (90mm) SKU: 301727 Brand: Advantec Size (mm): 90

Contenido visible del fabricante

Especificaciones KS 90 KS 90 ST KS 142 KS 142 ST KS 293 KS 293 ST KS 90 UH KS 142 UH KS 293 UH KST 47 KST 90 KST 142 Tamaño de filtro (mm) 90 142 293 90 142 293 47 90 142 Body 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 SS 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable O-ring & Gasket Silicone and PTFE Silicone and PTFE Silicone and PTFE Silicone Silicone Silicone Silicone and PTFE Silicone and PTFE Silicone and PTFE Inlet/Outlet ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 5/8” hose barb ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 16 mm hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter Max Pressure Inlet (psi) 99 99 99 99 99 99 71 71 71 Max Pressure Diff. (psi) <42 <42 <42 <42 <42 <42 <42 <42 <42 Filtration Area (cm 2) 45.3 113 530 45.3 113 530 12.5 43 113 Applications In-line gas or liquid filtration Ultraclean or sterilize gas or liquids Flow decay tests for pilot studies Hazardous toxicity testing and TCLP

Tabla fuente 1

	KS 90 KS 90 ST	KS 142 KS 142 ST	KS 293 KS 293 ST	KS 90 UH	KS 142 UH	KS 293 UH	KST 47	KST 90	KST 142
Tamaño de filtro (mm)	90	142	293	90	142	293	47	90	142
Body	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 SS	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable
O-ring & Gasket	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE	Silicone	Silicone	Silicone	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE
Inlet/Outlet	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 5/8” hose barb	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 16 mm hose barb adapter	¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter
Max Pressure Inlet (psi)	99	99	99	99	99	99	71	71	71
Max Pressure Diff. (psi)	<42	<42	<42	<42	<42	<42	<42	<42	<42
Filtration Area (cm 2)	45.3	113	530	45.3	113	530	12.5	43	113

301804

SKU Sterlitech	301804
Ficha del fabricante	Support screen (PTFE coated SS), KST 90 (90mm)
URL fuente	

Datos visibles del fabricante

Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile

Support screen (PTFE coated SS), KST 90 (90mm) SKU: 301804 Brand: Advantec Size (mm): 90

Contenido visible del fabricante

Especificaciones KS 90 KS 90 ST KS 142 KS 142 ST KS 293 KS 293 ST KS 90 UH KS 142 UH KS 293 UH KST 47 KST 90 KST 142 Tamaño de filtro (mm) 90 142 293 90 142 293 47 90 142 Body 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 SS 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable O-ring & Gasket Silicone and PTFE Silicone and PTFE Silicone and PTFE Silicone Silicone Silicone Silicone and PTFE Silicone and PTFE Silicone and PTFE Inlet/Outlet ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 5/8” hose barb ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 16 mm hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter Max Pressure Inlet (psi) 99 99 99 99 99 99 71 71 71 Max Pressure Diff. (psi) <42 <42 <42 <42 <42 <42 <42 <42 <42 Filtration Area (cm 2) 45.3 113 530 45.3 113 530 12.5 43 113 Applications In-line gas or liquid filtration Ultraclean or sterilize gas or liquids Flow decay tests for pilot studies Hazardous toxicity testing and TCLP

Tabla fuente 1

	KS 90 KS 90 ST	KS 142 KS 142 ST	KS 293 KS 293 ST	KS 90 UH	KS 142 UH	KS 293 UH	KST 47	KST 90	KST 142
Tamaño de filtro (mm)	90	142	293	90	142	293	47	90	142
Body	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 SS	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable
O-ring & Gasket	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE	Silicone	Silicone	Silicone	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE
Inlet/Outlet	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 5/8” hose barb	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 16 mm hose barb adapter	¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter
Max Pressure Inlet (psi)	99	99	99	99	99	99	71	71	71
Max Pressure Diff. (psi)	<42	<42	<42	<42	<42	<42	<42	<42	<42
Filtration Area (cm 2)	45.3	113	530	45.3	113	530	12.5	43	113

301905

SKU Sterlitech	301905
Ficha del fabricante	O-ring (silicone), KST 142 (142mm)
URL fuente	

Datos visibles del fabricante

O-ring (silicone), KST 142 (142mm) SKU: 301905 Brand: Advantec Size (mm): 142

Contenido visible del fabricante

Especificaciones KS 90 KS 90 ST KS 142 KS 142 ST KS 293 KS 293 ST KS 90 UH KS 142 UH KS 293 UH KST 47 KST 90 KST 142 Tamaño de filtro (mm) 90 142 293 90 142 293 47 90 142 Body 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 SS 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable O-ring & Gasket Silicone and PTFE Silicone and PTFE Silicone and PTFE Silicone Silicone Silicone Silicone and PTFE Silicone and PTFE Silicone and PTFE Inlet/Outlet ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 5/8” hose barb ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 16 mm hose barb adapter ¼” NPTM with 11 mm

hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter Max Pressure Inlet (psi) 99 99 99 99 99 99 71 71 71 Max Pressure Diff. (psi) <42 <42 <42 <42 <42 <42 <42 <42 <42 Filtration Area (cm 2) 45.3 113 530 45.3 113 530 12.5 43 113 Applications In-line gas or liquid filtration Ultraclean or sterilize gas or liquids Flow decay tests for pilot studies Hazardous toxicity testing and TCLP

Tabla fuente 1

	KS 90 KS 90 ST	KS 142 KS 142 ST	KS 293 KS 293 ST	KS 90 UH	KS 142 UH	KS 293 UH	KST 47	KST 90	KST 142
Tamaño de filtro (mm)	90	142	293	90	142	293	47	90	142
Body	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 SS	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable
O-ring & Gasket	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE	Silicone	Silicone	Silicone	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE
Inlet/Outlet	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 5/8” hose barb	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 16 mm hose barb adapter	¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter
Max Pressure Inlet (psi)	99	99	99	99	99	99	71	71	71
Max Pressure Diff. (psi)	<42	<42	<42	<42	<42	<42	<42	<42	<42
Filtration Area (cm 2)	45.3	113	530	45.3	113	530	12.5	43	113

301926

SKU Sterlitech	301926
Ficha del fabricante	Back pressure support screen (304 SS), KST 142 (142mm)
URL fuente	

Datos visibles del fabricante

Back pressure support screen (304 SS), KST 142 (142mm) SKU: 301926 Brand: Advantec Size (mm): 142

Contenido visible del fabricante

Especificaciones KS 90 KS 90 ST KS 142 KS 142 ST KS 293 KS 293 ST KS 90 UH KS 142 UH KS 293 UH KST 47 KST 90 KST 142 Tamaño de filtro (mm) 90 142 293 90 142 293 47 90 142 Body 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 SS 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable O-ring & Gasket Silicone and PTFE Silicone and PTFE Silicone and PTFE Silicone Silicone Silicone Silicone and PTFE Silicone and PTFE Silicone and PTFE Inlet/Outlet ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 5/8” hose barb ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 16 mm hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter Max Pressure Inlet (psi) 99 99 99 99 99 99 71 71 71 Max Pressure Diff. (psi) <42 <42 <42 <42 <42 <42 <42 <42 <42 Filtration Area (cm 2) 45.3 113 530 45.3 113 530 12.5 43 113 Applications In-line gas or liquid filtration Ultraclean or sterilize gas or liquids Flow decay tests for pilot studies Hazardous toxicity testing and TCLP

Tabla fuente 1

	KS 90 KS 90 ST	KS 142 KS 142 ST	KS 293 KS 293 ST	KS 90 UH	KS 142 UH	KS 293 UH	KST 47	KST 90	KST 142

Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile

Tamaño de filtro (mm)	90	142	293	90	142	293	47	90	142
Body	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 SS	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable
O-ring & Gasket	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE	Silicone	Silicone	Silicone	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE
Inlet/Outlet	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 5/8” hose barb	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 16 mm hose barb adapter	¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter
Max Pressure Inlet (psi)	99	99	99	99	99	99	71	71	71
Max Pressure Diff. (psi)	<42	<42	<42	<42	<42	<42	<42	<42	<42
Filtration Area (cm 2)	45.3	113	530	45.3	113	530	12.5	43	113

301990

SKU Sterlitech	301990
Ficha del fabricante	Multi-Media Pressure Sealing Holder, 142mm
URL fuente	

Datos visibles del fabricante

Multi-Media Pressure Sealing Holder, 142mm SKU: 301990 Brand: Advantec Diameter (mm): 142 Material Type: 304 Acero inoxidable

Contenido visible del fabricante

Especificaciones KS 90 KS 90 ST KS 142 KS 142 ST KS 293 KS 293 ST KS 90 UH KS 142 UH KS 293 UH KST 47 KST 90 KST 142 Tamaño de filtro (mm) 90 142 293 90 142 293 47 90 142 Body 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 SS 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable O-ring & Gasket Silicone and PTFE Silicone and PTFE Silicone and PTFE Silicone Silicone Silicone Silicone and PTFE Silicone and PTFE Silicone and PTFE Inlet/Outlet ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 5/8” hose barb ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 16 mm hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter Max Pressure Inlet (psi) 99 99 99 99 99 99 71 71 71 Max Pressure Diff. (psi) <42 <42 <42 <42 <42 <42 <42 <42 <42 Filtration Area (cm 2) 45.3 113 530 45.3 113 530 12.5 43 113 Applications In-line gas or liquid filtration Ultraclean or sterilize gas or liquids Flow decay tests for pilot studies Hazardous toxicity testing and TCLP

Tabla fuente 1

	KS 90 KS 90 ST	KS 142 KS 142 ST	KS 293 KS 293 ST	KS 90 UH	KS 142 UH	KS 293 UH	KST 47	KST 90	KST 142
Tamaño de filtro (mm)	90	142	293	90	142	293	47	90	142
Body	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 SS	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable
O-ring & Gasket	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE	Silicone	Silicone	Silicone	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE

Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile

Inlet/Outlet	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 5/8” hose barb	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 16 mm hose barb adapter	¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter
Max Pressure Inlet (psi)	99	99	99	99	99	99	71	71	71
Max Pressure Diff. (psi)	<42	<42	<42	<42	<42	<42	<42	<42	<42
Filtration Area (cm 2)	45.3	113	530	45.3	113	530	12.5	43	113

302002

SKU Sterlitech	302002
Ficha del fabricante	Underdrain support (316 SS), KST 142 (142mm)
URL fuente	

Datos visibles del fabricante

Underdrain support (316 SS), KST 142 (142mm) SKU: 302002 Brand: Advantec Size (mm): 142

Contenido visible del fabricante

Especificaciones KS 90 KS 90 ST KS 142 KS 142 ST KS 293 KS 293 ST KS 90 UH KS 142 UH KS 293 UH KST 47 KST 90 KST 142 Tamaño de filtro (mm) 90 142 293 90 142 293 47 90 142 Body 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 SS 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable O-ring & Gasket Silicone and PTFE Silicone and PTFE Silicone and PTFE Silicone Silicone Silicone Silicone and PTFE Silicone and PTFE Silicone and PTFE Inlet/Outlet ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 5/8” hose barb ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 16 mm hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter Max Pressure Inlet (psi) 99 99 99 99 99 99 71 71 71 Max Pressure Diff. (psi) <42 <42 <42 <42 <42 <42 <42 <42 <42 Filtration Area (cm 2) 45.3 113 530 45.3 113 530 12.5 43 113 Applications In-line gas or liquid filtration Ultraclean or sterilize gas or liquids Flow decay tests for pilot studies Hazardous toxicity testing and TCLP

Tabla fuente 1

	KS 90 KS 90 ST	KS 142 KS 142 ST	KS 293 KS 293 ST	KS 90 UH	KS 142 UH	KS 293 UH	KST 47	KST 90	KST 142
Tamaño de filtro (mm)	90	142	293	90	142	293	47	90	142
Body	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 SS	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable
O-ring & Gasket	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE	Silicone	Silicone	Silicone	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE
Inlet/Outlet	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 5/8” hose barb	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 16 mm hose barb adapter	¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter
Max Pressure Inlet (psi)	99	99	99	99	99	99	71	71	71
Max Pressure Diff. (psi)	<42	<42	<42	<42	<42	<42	<42	<42	<42

Importadora Gyb Limitada
Padre orellana 1476
Santiago CL13101 Chile

Filtration Area (cm 2)	45.3	113	530	45.3	113	530	12.5	43	113

306108

SKU Sterlitech	306108
Ficha del fabricante	Inlet cap gasket/O-ring (silicone), KST 47 (47mm)
URL fuente	

Datos visibles del fabricante

Inlet cap gasket/O-ring (silicone), KST 47 (47mm) SKU: 306108 Brand: Advantec Size (mm): 47

Contenido visible del fabricante

Especificaciones KS 90 KS 90 ST KS 142 KS 142 ST KS 293 KS 293 ST KS 90 UH KS 142 UH KS 293 UH KST 47 KST 90 KST 142 Tamaño de filtro (mm) 90 142 293 90 142 293 47 90 142 Body 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 Acero inoxidable 304 SS 304 or 316 Acero inoxidable 304 or 316 Acero inoxidable O-ring & Gasket Silicone and PTFE Silicone and PTFE Silicone and PTFE Silicone Silicone Silicone Silicone and PTFE Silicone and PTFE Silicone and PTFE Inlet/Outlet ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb) ¾” NPTF and NPTM to 5/8” hose barb ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 11 mm hose barb adapter ¾” NPTF and NPTM with 16 mm hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter ¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter Max Pressure Inlet (psi) 99 99 99 99 99 99 71 71 71 Max Pressure Diff. (psi) <42 <42 <42 <42 <42 <42 <42 <42 <42 Filtration Area (cm 2) 45.3 113 530 45.3 113 530 12.5 43 113 Applications In-line gas or liquid filtration Ultraclean or sterilize gas or liquids Flow decay tests for pilot studies Hazardous toxicity testing and TCLP

Tabla fuente 1

	KS 90 KS 90 ST	KS 142 KS 142 ST	KS 293 KS 293 ST	KS 90 UH	KS 142 UH	KS 293 UH	KST 47	KST 90	KST 142
Tamaño de filtro (mm)	90	142	293	90	142	293	47	90	142
Body	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 Acero inoxidable	304 SS	304 or 316 Acero inoxidable	304 or 316 Acero inoxidable
O-ring & Gasket	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE	Silicone	Silicone	Silicone	Silicone and PTFE	Silicone and PTFE	Silicone and PTFE
Inlet/Outlet	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 3/8” hose barb (ST Models: 1.5" Sanitary fitting to 14.3 mm hose barb)	¾” NPTF and NPTM to 5/8” hose barb	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 11 mm hose barb adapter	¾” NPTF and NPTM with 16 mm hose barb adapter	¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter	¼” NPTM w/ ball valve stepped (7, 10.5, 13 mm) hose barb adapter ¼” NPTM with 11 mm hose barb adapter
Max Pressure Inlet (psi)	99	99	99	99	99	99	71	71	71
Max Pressure Diff. (psi)	<42	<42	<42	<42	<42	<42	<42	<42	<42
Filtration Area (cm 2)	45.3	113	530	45.3	113	530	12.5	43	113

Siguiente paso: ver producto en Cotecno | solicitar cotización