

Rotor oscilante para centrifuga 4*500 ml (bioseguridad)

Código: B2-01-010384-R37

Marca: N/D

[Ver producto en Cotecno](#) | [Solicitar cotización](#)

[Detalle](#) | [Especificaciones](#) | [Aplicaciones](#)

Detalle

Swing Rotor

Especificaciones técnicas

Especificación	-R37
Tipo de rotor	Rotor oscilante
Volumen	4*500ml(bioseguridad)
Velocidad máxima (rpm)	4000
FCR máxima (xg)	3399
Adaptadores	48*2/3/4/5/7ml tubo de recolección de sangre, 64*2/3/4/5/7ml tubo de recolección de sangre, 36*10ml(●), 36*10ml(▲), 36*15ml(●), 36*15ml(▲), 12*50ml(●), 12*50ml(▲), 16*50ml(●), 16*50ml(▲), 48*15ml(▲), 4*250ml, 32*15ml(▲), 48*10ml(●)

Aplicaciones

1. Check capacity

Check that the stated rotor type and capacity match the tube format you need to use.

- **Rotor Type:** Swing Rotor
- **Volume:** 4*500ml(biosafety)

2. Check performance

Compare the stated maximum speed and maximum RCF with your procedure requirements.

- **Max. Speed(rpm):** 4000
- **Max. RCF(xg):** 3399

Siguiente paso: [ver producto en Cotecno](#) | [solicitar cotización](#)