

HARMSCO HOUSING FSSS -1A-222 SINGLE CARTRIDGE HOUSING



SKU: FSSS-1A-222 | **Categorías:** [Equipo Analítico](#) |

DESCRIPCIÓN DEL PRODUCTO

HARMSCO HOUSING FSSS -1A-222 SINGLE CARTRIDGE HOUSING

Part Number: FSSS-1A-222



Especificaciones

Marca	Harmsco Housing FSSS
Configuración	222/flat
Presión de trabajo bar	20.7
Presión psi	300
Temperatura máxima de °C	121
Temperatura máxima de °F	250
Material	316 Stainless Steel
O-Ring / juntas /	EPDM

Dimensiones / Pesos

Entrada inch	3/4
Salida pulgadas	3/4
Longitud del cartucho inch	9-3/4
diámetro exterior pulgada	Ø4,06
Altura pulgadas	13

Aplicación

Food & Beverage, Process water, RO Pre-filtration, Lubricants



FSSS Series Filter Housings are designed with a double o-ring compression which allows for positive sealing and easy access. Offered in DOE (double open end), 222/Flat and 226/Flat configurations.

304 or 316 stainless steel construction

300 PSI (20.7 bar) pressure rating

Electropolished finish

Offered in Double Open End 222 / Flat

or 226 / Flat configurations

Double o-ring compression seal for easy
change out

Includes 1/4" NPT drain

Inline design for easy installation

Standard with wrench and mounting bracket

Knife edge seal at both cartridge ends to
eliminate by-pass for DOE cartridges

[Ver PDF](#)

INFORMACIÓN ADICIONAL

COTECNO