

SENSOR DE TEMPERATURA DE LÍQUIDO



SKU: B-01-05-0514 | **Categorías:** [Detector de suelos y líquidos](#) |

GALERÍA DE IMÁGENES



DESCRIPCIÓN DEL PRODUCTO

- [Descripción](#)

Se utiliza para medir la temperatura del medio líquido, aplicado a la estación meteorológica automática, detección de temperatura del agua de estanque o depósito y otros campos. Sensor con resistencia térmica de precisión como componente de detección, muestreo de señal incorporado y función de amplificación, deriva cero y compensación de temperatura, tiene las características de alta precisión de medición y buena estabilidad.[image_with_animation image_url="163366" alignment="center" animation="Fade In" hover_animation="none" border_radius="none" box_shadow="none" image_loading="default" max_width="100%" max_width_mobile="default"]

Especificaciones

| Modelo | B-01-05-0514 |
|---------------------------------|------------------------|
| Artículo | Especificación técnica |
| Rango | -40- + 80 °C |
| Suministro | 12-24 V CC |
| Precisión | ± 0,5 °C |
| Tiempo de respuesta | <1 s |
| Señal de salida | 4-20 mA, 0-5 V, RS485 |
| Temperatura de funcionamiento | -40 °C - + 80 °C |
| Material de la carcasa | 316L |
| Peso de la sonda (sin embalaje) | 145 g |
| Protección de ingreso | IP68 |
| Almacenamiento | 10-60 °C @ 20% -90% RH |

Detalles de producto

[image_with_animation image_url="163722" alignment="center" animation="Fade In" hover_animation="none" border_radius="none" box_shadow="none" image_loading="default" max_width="100%" max_width_mobile="default"] [image_with_animation image_url="163723" alignment="center" animation="Fade In" hover_animation="none" border_radius="none" box_shadow="none" image_loading="default" max_width="100%" max_width_mobile="default"]



max_width_mobile="default"]

Entorno aplicable

El diseño especial hace que el B-01-05-0514 sea adecuado para diferentes entornos.

[image_with_animation image_url="163627" alignment="center" animation="Fade In" hover_animation="none" border_radius="none" box_shadow="none" image_loading="default" max_width="100%" max_width_mobile="default"]

Aplicación de producto

[image_with_animation image_url="163630" alignment="center" animation="Fade In" hover_animation="none" border_radius="none" box_shadow="none" image_loading="default" max_width="100%" max_width_mobile="default"]

COTECNO