VACUUM FILTRATION SYSTEM

ROCKER 300 – SF 30



Model	Rocker 300 – SF 30	
VOLTAGE	110V/60Hz	220V/50Hz
Max. Power	65W	60W
Max. Current	0.7A	0.3A
Max. Vacuum	99 mbar	
Max. Flow Rate	23 L/min	20 L/min
Motor Rotation Speed	1750 RPM	1450 RPM
Horse Power	1/8 HP	
Noise Level	50 dB	
Hose Barb	ID8 (5/16 inch)	
Vacuum Regulator	Yes	
Overflow Protection	Yes	
Thermal Protection	Yes	

Features

NO AIR POLLUTION, MAINTENANCE FREE

Rocker 300 vacuum pumps are piston-driven, no need for lubricant, regular oil changes and maintenance with no oil pollution.

OVERFLOW PROTECTION

Both Rocker 300 and the waste bottle come with a built-in overflow protection to keep the filtrate from overflowing when bottle is full.

AUTOCLAVABLE AND SHATTERPROOF

The waste bottle and filter holder are made of engineering plastics or SS316 stainless steel which are shatterproof, high temperature resistance and autoclavable.

HOOP HOLDER

Equipped with Rocker Hoop bottle holder. Spill-free and care-free, improve laboratory safety.

INTERNATIONAL CERTIFICATION

- CE certification
- CSA certification
- IP30 protection
- RoHS certification

Applications

- Microbial detection

 Copyright © 2025