VACUUM FILTRATION SYSTEM

ROCKER 300 – LF 31



Model	Rocker 300 – LF 31	
VOLTAGE	110V/60Hz	220V/50Hz
Max. Power	65W	60W
Max. Current	0.7A	0.3A
Max. Vacuum	99 mbar	
Max. Flow Rate	23 L/min	20 L/min
Motor Rotation Speed	1750 RPM	1450 RPM
Horse Power	1/8 HP	
Noise Level	50 dB	
Hose Barb	ID8 (5/16 inch)	
Vacuum Regulator	Yes	
Overflow Protection	Yes	
Thermal Protection	Yes	

Features

NO AIR POLLUTION, MAINTENANCE FREE

Rocker series pumps are piston-driven, no need for lubricant, regular oil changes and maintenance with no oil pollution.

THE PATENTED SPIN-LOCK DESIGN

The filter holder can be connected with waste bottle by patented spin-lock connection giving a fast and stable installation without clamp.

OVERFLOW PROTECTION

The waste bottle of Rocker 300 – LF 31 comes with a built-in overflow protection to keep the filtrate from overflowing when waste bottle is full.

INTERNATIONAL CERTIFICATION

- CE certification
- CSA certification
- IP30 protection
- RoHS certification

Applications

- Vacuum filtration

 Copyright © 2025