VACUUM FILTRATION SYSTEM

ROCKER 300 – LF 30



Model	Rocker 300 – LF 30	
VOLTAGE	110V/60Hz	220V/50Hz
Max. Power	65W	60W
Max. Vacuum	99 mbar	
Max. Flow Rate	23 L/min	20 L/min
Noise Level	50 dB	
Hose Barb	ID8 (5/16 inch)	
Vacuum Regulator	Yes	
Overflow Protection	Yes	
Thermal Protection	Yes	

Features

OIL-FREE & CARE-FREE

Rocker pumps are driven by piston that needs no lubricant, making them maintenance-free and oil-mist-free.

CLAMP-FREE WITH SPIN-LOCK

LF 30 bottles are equipped with LF filter holders that can be mounted with revolutionary spin-lock and totally clamp-free.

OVERFLOW PROTECTION

Waste bottle comes with a built-in overflow protection to keep the filtrate from overflowing when waste bottle is full.

HOOP HOLDER

Equipped with Rocker Hoop bottle holder. Spill-free and care-free, improve laboratory safety.

INTERNATIONAL CERTIFICATION

- CE certification
- UKCA certification
- CSA certification
- IP30 protection
- RoHS certification

Applications

- Suspended solid test
- Vacuum filtration

 Copyright © 2025