WATERVAC FILTRATION SYSTEM

WATERVAC 200 – MS



Model	WaterVac 200 - MS
PERFORMANCE DATA	
Max. Vacuum	313 mbar abs.
Max. Liquid Flow Rate	4.5 L/min
Hose Barb	ID8
Noise Level	60 dB
Net Weight	2.8 Kg
Dimension (LxWxH)	21 x 18 x 26 cm
Material Contact With Filtrate	SS316, FKM, Silicone, PP, PPS
ELECTRICAL DATA	
Power Input	DC24V, 1.8A
Max. Power	44W
Motor	Brushless DC Motor (BLDC)
Safety	Overheat Protection
OTHER DATA	
Number of Branch	1
Adaptor	No. 8 Stopper
Filter Holder	(Optional) MF 3/ MF 5, Magnetic filter holder, 300 mL / 500 mL

Features

SAVE 70% BENCH SPACE

WaterVac 200 is a revolutionary filtration system that integrates filter holders with a liquid pump that bypasses liquid directly to waste. Kiss all tubes and bottles goodbye.

IMPROVE EFFICIENCY

Built-in liquid pump transfers filtered liquid directly to waste, saving time for emptying and cleaning bottles.

COMPLIANCE WITH ISO 8199

WaterVac 200 complies with ISO 8199 regulation and ideal for microbiological sample filtration. (*ISO8199: Water quality – General guidance for microbiological examinations by culture)

VERSATILE & COMPATIBLE

Replaceable adaptors make WaterVac 200 compatible with most available filter funnels and holders.

INTERNATIONAL CERTIFICATION

- CE certification
- UKCA certification
- IP 41 protection class
- RoHS certification

Applications

- Microbiological test by Membrane Filter Technique
- Suspended solid test for water monitoring
- General filtration without collecting filtrate

Compatibility

Compatible with various kinds of adaptor and filter holder



 Copyright © 2025